



# TruLaser Tube 3000 fiber

Technical data

## TruLaser Tube 3000 fiber

### ROUND TUBE

|                                     |                     |
|-------------------------------------|---------------------|
| MAXIMUM OUTSIDE DIAMETER            | 152 mm              |
| MAXIMUM OUTSIDE DIAMETER (OPTIONAL) | 170 mm <sup>1</sup> |

### RECTANGULAR PROFILE

|   |                 |
|---|-----------------|
| MAXIMUM SIDE LENGTH AND OUTER CIRCLE DIAMETER | 152 mm / 170 mm |
|---|-----------------|

### MAXIMUM RAW MATERIAL LENGTH FOR AUTOMATIC LOADING

|                           |                      |
|---------------------------|----------------------|
| FOR LOADMASTER TUBE 6.5 M | 6500 mm              |
| FOR LOADMASTER TUBE 8.0 M | 8000 mm <sup>2</sup> |

### FINISHED PART LENGTH

|                                |                      |
|--------------------------------|----------------------|
| FOR UNLOADING UNIT 3 M         | 3000 mm              |
| FOR UNLOADING UNIT 3 M + 1.5 M | 4500 mm <sup>2</sup> |

### WORKPIECE WEIGHT

|   |                    |
|---|--------------------|
| MAXIMUM PATH WEIGHT (STANDARD/OPTIONAL) | 18.5 kg/m / - kg/m |
|---|--------------------|

### MAXIMUM RAW MATERIAL WEIGHT WITH AUTOMATIC LOADING

|                            |        |
|----------------------------|--------|
| WITH LOADMASTER TUBE 6.5 M | 120 kg |
| WITH LOADMASTER TUBE 8.0 M | 148 kg |

## Footnotes

---

1 — Round tubes with a diameter of 152 mm to 170 mm can only be manually loaded.

2 — Value for extended versions (option)